

Product type designation

TIM 4R-IE

SINAUT ST7, TIM 4R-IE communication module for SIMATIC S7-300, S7-400, PC; with two RS232/RS485 interfaces for SINAUT Communication via standard WAN and two RJ45 interfaces for SINAUT communication via IP-based networks (WAN or LAN)



Figure similar

Transmission rate

Transfer rate

- | | |
|---------------------------|--------------------|
| • for Industrial Ethernet | 10 ... 100 Mbit/s |
| • acc. to RS 232 | 50 ... 38400 bit/s |

Interfaces

Number of interfaces / acc. to Industrial Ethernet	2
Number of electrical connections	
• for external data transmission / acc. to RS 232	2
• for power supply	1
Type of electrical connection	
• of Industrial Ethernet interface	RJ45 port
• at interface 1 / for external data transmission	9 pin Sub-D-connector, RS232 switchable to RS485
• at interface 2 / for external data transmission	9-pole D-sub connector, RS232 can be switched to RS485
• for power supply	2-pole plugable terminal block
design of the removable storage / C-PLUG	Yes

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage	24 V
Supply voltage	20.4 ... 28.8 V
Supply voltage / external / at DC / Rated value	24 V
Supply voltage / external / at DC / rated value	20.4 ... 28.8 V
Consumed current	
<ul style="list-style-type: none"> • from backplane bus / at DC / at 24 V / maximum 	0.2 A
<ul style="list-style-type: none"> • from external supply voltage / at DC / at 24 V / maximum 	0.17 A
Power loss [W]	4.6 W
Product extension / optional / Backup battery	Yes
Type of battery	Lithium AA / 3.6 V / 2.3 Ah
Backup current	
<ul style="list-style-type: none"> • typical 	100 µA
<ul style="list-style-type: none"> • maximum 	160 µA

Permitted ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> • during operation 	0 ... 60 °C
<ul style="list-style-type: none"> • during storage 	-40 ... +70 °C
<ul style="list-style-type: none"> • during transport 	-40 ... +70 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Module format	Compact module S7-300 double width
Width	80 mm
Height	125 mm
Depth	120 mm
Net weight	0.4 kg

Product properties, functions, components / general

Number of units	
<ul style="list-style-type: none"> • Note 	Number of TIM 4R-IE per S7-300/S7-400: multiple, number depends on the connection resources of the CPU
Wire length	
<ul style="list-style-type: none"> • with RS 232 interface / maximum 	6 m
<ul style="list-style-type: none"> • with RS 485 interface / maximum 	30 m

Performance data / S7 communication

Number of possible connections / for S7 communication	
<ul style="list-style-type: none"> • maximum 	64

<ul style="list-style-type: none"> • with PG connections / maximum • with OP connections / maximum 	<p>2</p> <p>62</p>
Service <ul style="list-style-type: none"> • SINAUT ST7 via S7 communication • PG/OP communication 	<p>Yes</p> <p>Yes</p>
Performance data / multi-protocol mode	
Number of active connections / with multi-protocol mode	128
Performance data / telecontrol	
Suitability for use <ul style="list-style-type: none"> • Node station • substation • TIM control center 	<p>Yes</p> <p>Yes</p> <p>Yes</p>
Protocol / is supported <ul style="list-style-type: none"> • TCP/IP • DNP3 • SINAUT ST1 protocol • SINAUT ST7 protocol 	<p>Yes</p> <p>No</p> <p>Yes</p> <p>Yes</p>
Product function / data buffering if connection is aborted	Yes; 56,000 data messages
Storage capacity <ul style="list-style-type: none"> • of S7 CPU RAM / for TD7onCPU mode data blocks on CPU / required • of S7 CPU RAM / for TD7onTIM mode data blocks on TIM / required • Note 	<p>20 Kibyte</p> <p>0 Kibyte</p> <p>TD7onCPU: at least 20 KB, actual requirement determined by data volume and functional scope TD7onTIM: 0 bytes in most favorable case</p>
Product feature / Buffered message frame memory	Yes
Transmission format <ul style="list-style-type: none"> • for SINAUT ST1 protocol with polling / 11 bit • for SINAUT ST1 protocol with spontaneous / 10-bit or 11-bit • for SINAUT ST7 protocol with multi-master polling / 10-bit • for SINAUT ST7 protocol with polling or spontaneous / 10-bit or 11-bit 	<p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p>
Operating mode for scanning of data transmission <ul style="list-style-type: none"> • with dedicated line/radio link / with SINAUT ST1 protocol • with dedicated line/radio link / with SINAUT ST7 protocol 	<p>Polling, polling with time slot procedure</p> <p>Polling, polling with time slot procedure, multi-master polling with time slot procedure</p>

<ul style="list-style-type: none"> • with dial-up network / with SINAUT ST1 protocol 	spontaneous
<ul style="list-style-type: none"> • with dial-up network / with SINAUT ST7 protocol 	spontaneous
Hamming distance	
<ul style="list-style-type: none"> • for SINAUT ST1 protocol 	4
<ul style="list-style-type: none"> • for SINAUT ST7 protocol 	4
Configuration software	
<ul style="list-style-type: none"> • required 	SINAUT ST7 ES
<ul style="list-style-type: none"> • for CPU configuring / required / SINAUT TD7 block library for CPU 	Yes
<ul style="list-style-type: none"> • for PG configuring / required / SINAUT ST7 configuration software for PG 	Yes
Storage location / of TIM configuration data	on internal TIM flash memory, or on TIM in optional C-PLUG, or on MMC of the S7-300 CPU if TIM installed in S7-300 controller

Product functions / Security

Suitability for operation / Virtual Private Network	Yes
Type of authentication / with Virtual Private Network / PSK	Yes
Product function	
<ul style="list-style-type: none"> • password protection for VPN 	Yes
<ul style="list-style-type: none"> • MSC client via GPRS modem with MSC capability 	Yes
Protocol	
<ul style="list-style-type: none"> • is supported / MSC protocol 	Yes
<ul style="list-style-type: none"> • with Virtual Private Network MSC / is supported 	TCP/IP
Key length / for MSC / with Virtual Private Network	128 bit
Number of possible connections	
<ul style="list-style-type: none"> • as MSC client / with VPN connection 	1
<ul style="list-style-type: none"> • as MSC server / with VPN connection 	128

Product functions / Time

Product component / Hardware real-time clock	Yes
Product feature / Hardware real-time clock w. battery backup	Yes
Accuracy / of the hardware real-time clock / per day / maximum	4 s
time synchronization	
<ul style="list-style-type: none"> • from NTP-server 	Yes

Accessories

Further Information / Internet Links

Internet-Link	
---------------	--

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/snst>

<http://www.siemens.com/simatic-net>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

07/10/2018